

Product information 74RAct WD3 LED3300 ETDD
TOC: 6860951



Luminaire type

Round surface-mounted LED luminaire with opal PMMA diffuser. Luminaire with Activ equipment for controlling light colour via separate control unit.

Applications

For entrance areas, corridors, stairways, lounges, hotels, restaurants and residential zones.

Mounting methods

For wall or ceiling mounting.

Optical system

With round, spherically-shaped diffuser, slightly flattened on the luminaire head, opal.

LED system

LED panels configured with warm white and daylight white light colour LEDs. Light colour variable, warm white - daylight white, colour temperature variable, 2700 K - 6500 K, colour rendering index Ra > 80. Service life L₈₀ (t_q 25 °C) = 50,000 h.

Luminaire body


Luminaire body of sheet steel, white, powder-coated. Diameter of diffuser Ø 520 mm.

Electrical version

With electronic transformer, digitally dimmable (DALI).

Specification text

Round surface-mounted LED luminaire with opal PMMA diffuser. Luminaire with Activ equipment for controlling light colour via separate control unit. For wall or ceiling mounting. With round, spherically-shaped diffuser, slightly flattened on the luminaire head, opal. LED panels configured with warm white and daylight white light colour LEDs. Light colour variable, warm white - daylight white, colour temperature variable, 2700 K - 6500 K, colour rendering index Ra > 80. Service life L₈₀ (t_q 25 °C) = 50,000 h. Luminaire body of sheet steel, white, powder-coated. Diameter of diffuser Ø 520 mm. Safety class I, protection rating IP40, impact resistance IK02/0,2 J, heat resistance 650 °C. With electronic transformer, digitally dimmable (DALI).



file TX051336
 UGR I = 20.8
 UGR q = 20.8
 LFEC = F0

— c0-c180
 — c90-c270



Colour	white (...01)
Weight	2.65 kg
Safety class	I
Hot wire test	650 °C
Impact resistance	0,2 J
Degree of protection	IP20
LFEC	F0
Cibse	BZ 5
LOR	1,00

