

DAC240 LED

134-1439

1/4

we-ef



Description

IP65, Class I, IK07. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Silicone rubber gasket. PMMA-LED lens array. Safety glass lens, hinged. Frame with safety catch. Two cable entries.

Beam Type	-
Lamp Type	LED-24/48W / 700 mA - 4000 K
Gear Type	EC
Nominal Luminous Flux (lm)	
LED Lumens	246 lm
LEDs	24
Total Lumens	5903 lm
Tj	85 °C
Rated Luminous Flux (lm)	
LED Lumens	227.7 lm
Total Lumens	5464.3 lm
Ta	25 °C
Rated Input Power	55 W

DAC240 LED

134-1439

3/4

we-ef

Optical Accessories

Surface wash lens IO-360

Broadens light distribution in all planes. Does not fit in combination with [B] lens.

C1

■ **134-1441** Flood lens IO-360

191



C1

Linear spread lens IO-180

Broadens light distribution in one plane only. Internal component, factory installed.

C1

■ **134-1382** Linear spread lens IO-180

191



C1

Wallwash lens IO-20

Specifically developed for the lighting of architectural surfaces, in combination with WE-EF [M] symmetric medium beam LED optics. Luminaires fitted with the IO-20 wallwash lens are typically positioned at $0.125 \times h$ away from the target surface and spaced up to $1.75 \times d$ apart: h = height of wall/target surface $d = 0.125 \times h$ = distance from the wall/target surface $s = 1.75 \times d$ = spacing between luminaires The IO-20 LED wallwash lens is factory-installed within the luminaire. The factory-sealed qualities and advantages of the luminaire are fully maintained.

DAC240 LED

134-1439

4/4



C1

■ **134-1492** Wallwash lens 10-20°

191



C1