

RMT320 Two-sided

105-7002

1/2

we-ef



Description

[Factory-sealed] Pole mounted luminaire. IP66. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Powdercoat finish in black RAL 9004, grey aluminium RAL 9007 or white RAL 9016. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Maximum spacing for pathway and streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height. The two-sided light output versions are available with one or two circuits. Two circuits allow separate switching.

Beam Type	Streetlighting distribution [S70]
------------------	-----------------------------------

Lamp Type	LED-24/72W / 1050 mA - 4000 K
------------------	-------------------------------

Gear Type	EC
------------------	----

Nominal Luminous Flux (lm)

LED Lumens	450 lm
------------	--------

LEDs	24
------	----

Total Lumens	10800 lm
--------------	----------

Tj	85 °C
----	-------

Rated Luminous Flux (lm)

LED Lumens	414.1 lm
------------	----------

Total Lumens	9937.3 lm
--------------	-----------


Ta	25 °C
----	-------

Rated Input Power	83 W
--------------------------	------

RMT320 Two-sided

105-7002

2/2



Missing Image