

Product information 74R WD1 LED1000-840 ETDD TOC: 6857851



Luminaire type

Round surface-mounted LED luminaire with opal PMMA diffuser.

Applications

For entrance areas, corridors, stairways, lounges, hotels, restaurants and residential zones.

Mounting methods

For wall or ceiling mounting.

Optical system

With round, spherically-shaped diffuser, slightly flattened on the luminaire head, opal.

LED system

Luminaire luminous flux 1400 lm, connected load 13 W, luminous efficiency of luminaire 108 lm/W. Light colour neutral white, colour temperature 4000 K, colour rendering index $R_a > 80$. Service life $L_{80}(t_q 25^\circ\text{C}) = 50,000$ h.

Luminaire body


Luminaire body of sheet steel, white, powder-coated. Diameter of diffuser $\varnothing 320$ mm.

Electrical version

With electronic transformer, digitally dimmable (DALI).

Specification text

Round surface-mounted LED luminaire with opal PMMA diffuser. For wall or ceiling mounting. With round, spherically-shaped diffuser, slightly flattened on the luminaire head, opal. Luminaire luminous flux 1400 lm, connected load 13 W, luminous efficiency of luminaire 108 lm/W. Light colour neutral white, colour temperature 4000 K, colour rendering index $R_a > 80$. Service life $L_{80}(t_q 25^\circ\text{C}) = 50,000$ h. Luminaire body of sheet steel, white, powder-coated. Diameter of diffuser $\varnothing 320$ mm. Safety class I, protection rating IP40, impact resistance IK02/0,2 J, heat resistance 650°C . With electronic transformer, digitally dimmable (DALI).



file TX050619
UGR I = 19.1
UGR q = 19.1
LFEC = F0

— c0-c180
— c90-c270



Colour	white (...01)
Safety class	I
Hot wire test	650 °C
Impact resistance	0,2 J
Degree of protection	IP40
LFEC	F0
Cibse	BZ 5
LOR	1,00

