







MIOVA

oktalite

Type of luminaire	Recessed luminaires
Application areas	Wide-area merchandise illumination
Pan/tilt range	fixed
Mounting	spring mounting
Ceiling thickness	1 - 25 mm
Lighting technology	LED
Lumen category	3000 lm - 5000 lm
Light colour White	2700 K, 3000 K, 3100 K Best Colour, 3100 K Efficient Colour, 3500 K, 4000 K
Cooling	passive
Supply unit	driver separate
Luminaire colour	RAL 9005 jet black RAL 9006 white aluminium RAL 9016 traffic white Special colours on request
Surface	structure powder-coated
Nominal voltage	220 - 240 V, 50/60Hz
lighting controls	on request
Weight	approx. 1.0 kg
Components	 Luminaire housing  Supply unit
Test seal	  




Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T +49 221 59767-0 · F +49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2018-03-15



**MIOVA****oktalite**

Lumen category	Light colour	CRI [RA]	system luminous flux	System performance	Reflector colour	Order number		
						white	silver	black
3000 lm	2700 K	82	2545 lm	24 W	silver	10172990	10172991	10172992
3000 lm	3000 K	83	2740 lm	24 W	silver	10172993	10172994	10172995
3000 lm	3100 K Best Colour	95	2850 lm	32 W	silver	10175060	10175061	10175062
3000 lm	3100 K Efficient Colour	84	2665 lm	24 W	silver	10172996	10172997	10172998
3000 lm	3500 K	84	2780 lm	24 W	silver	10172999	10173000	10173001
3000 lm	4000 K	84	2830 lm	24 W	silver	10173002	10173003	10173004
4000 lm	2700 K	82	3285 lm	32 W	silver	10172990	10172991	10172992
4000 lm	3000 K	83	3535 lm	32 W	silver	10172993	10172994	10172995
4000 lm	3100 K Best Colour	95	3575 lm	42 W	silver	10175060	10175061	10175062
4000 lm	3100 K Efficient Colour	84	3435 lm	32 W	silver	10172996	10172997	10172998
4000 lm	3500 K	84	3585 lm	32 W	silver	10172999	10173000	10173001
4000 lm	4000 K	84	3650 lm	32 W	silver	10173002	10173003	10173004
5000 lm	2700 K	82	4120 lm	42 W	silver	10172990	10172991	10172992
5000 lm	3000 K	83	4440 lm	42 W	silver	10172993	10172994	10172995
5000 lm	3100 K Efficient Colour	84	4315 lm	42 W	silver	10172996	10172997	10172998
5000 lm	3500 K	84	4495 lm	42 W	silver	10172999	10173000	10173001
5000 lm	4000 K	84	4585 lm	42 W	silver	10173002	10173003	10173004

**Beam angle**

Wall Washer

Reflector colour

silver

Light colour

2700 - 4000 K

LOR

82 %

Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T +49 221 59767-0 · F +49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2018-03-15



Supply unit - LED

driver

oktalite

Connection type	Pre-wired plug-in connectivity
Mains connection	GST 18i3
Luminaire connection	Tyco
Cable length secondary	400 mm
Nominal voltage	220 - 240 V, 50/60Hz
Schutzart_EN	IP20
Schutzklasse_EN	I, II
lighting controls	on request
Lighting technology	LED

Lighting technology	Output	System performance	Order number
LED	600 mA	24 W	10163909
LED	800 mA	32 W	10163912
LED	1050 mA	42 W	10163914

Technical details as well as weight specifications and measurements have been prepared with care. Errors excepted. All dimensions in mm · LED service life data: L80/B10 at ambient temperature (ta) 25°C. Rated lamp service life 50,000h. Luminous flux and efficiency specifications are subject to a tolerance of +/- 10%. Min CRI Ra: >80 / >90 · Product images are used as an example and may differ from the original · We reserve the right to make changes, insofar as they serve progress. Oktalite Lichttechnik GmbH · Mathias-Brüggen-Str. 73 · 50829 Cologne · T +49 221 59767-0 · F +49 221 59767-40 · mail@oktalite.com · www.oktalite.com · 2018-03-15

