

# RMT320 One-sided

105-7045

1/2

**we-ef**



## Description

[Factory-sealed] Pole mounted luminaire. IP66. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Powdercoat finish in black RAL 9004, grey aluminium RAL 9007 or white RAL 9016. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Maximum spacing for pathway and streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height. The two-sided light output versions are available with one or two circuits. Two circuits allow separate switching.

<b>Beam Type</b>	rectangular, forward-throw beam [R65]
------------------	---------------------------------------

<b>Lamp Type</b>	LED-12/52W / 1400 mA - 4000 K
------------------	-------------------------------

<b>Gear Type</b>	EC
------------------	----

## Nominal Luminous Flux (lm)

LED Lumens	575.6 lm
------------	----------

LEDs	12
------	----

Total Lumens	6907 lm
--------------	---------

Tj	85 °C
----	-------

## Rated Luminous Flux (lm)

LED Lumens	469.9 lm
------------	----------

Total Lumens	5638.2 lm
--------------	-----------

Ta	25 °C
----	-------

<b>Rated Input Power</b>	59 W
--------------------------	------

# RMT320 One-sided

105-7045

2/2

