



Description

IP66, Class I. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Including 6.0 m of flexible mains cable. IP68 cable connector. Integral EC electronic converter, including 6/6 kV surge protection One LED concept optics for superior illumination and glare control. Maximum spacing for pathway and streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height.

Beam Type	asymmetric, side-throw beam [P65]
Lamp Type	LED-24/72W / 1050 mA - 3000 K
Gear Type	EC
Nominal Luminous Flux	

(lm)		
LED Lumens	390 lm	
LEDs	24	
Total Lumens	9360 lm	
	85 °C	

Rated Luminous Flux (Im)

Τj


LED Lumens	343.8 lm
Total Lumens	8251.4 lm
Ta	25 °C
Rated Input Power	83 W


RMM320

105-9977

2/2







Material Specification

Body:	Marine-grade, die-cast aluminium alloy
Weight (kg):	10.00
Gasket:	Silicone CCG® Controlled Compression Gasket
Ingress protection:	IP66
Impact protection:	IK09
Corrosion protection:	5CE

Electrical Specification

Ballast:	Integral EC electronic converter
Cable:	Including 6 m of cable