

# RMT320 One-sided

105-9900

1/2

**we-ef**



## Description

[Factory-sealed] Pole mounted luminaire. IP66. IK09. Marine-grade, die-cast aluminium alloy. 5CE superior corrosion protection including PCS hardware. Powdercoat finish in black RAL 9004, grey aluminium RAL 9007 or white RAL 9016. RFC™ Reflection Free Contour main lens. Silicone CCG® Controlled Compression Gasket. Luminaire is factory-sealed and does not need to be opened during installation. Integral EC electronic converter. Advanced thermal management protects LEDs while optimising lumens output. Removable LED boards for upgrading. CAD-optimised OLC® One LED Concept optics for superior illumination and glare control. Maximum spacing for pathway and streetlighting applications depends on wattage and light distribution: 5.5 to 9 times the mounting height. The two-sided light output versions are available with one or two circuits. Two circuits allow separate switching.

<b>Beam Type</b>	Streetlighting distribution [S70]
------------------	-----------------------------------

<b>Lamp Type</b>	LED-6/6W / 4000 K
------------------	-------------------

<b>Gear Type</b>	EC
------------------	----

## Nominal Luminous Flux (lm)

LED Lumens	134.5 lm
------------	----------

LEDs	6
------	---

Total Lumens	807 lm
--------------	--------

Tj	85 °C
----	-------

## Rated Luminous Flux (lm)

LED Lumens	123.2 lm
------------	----------

Total Lumens	739 lm
--------------	--------

Ta	25 °C
----	-------

<b>Rated Input Power</b>	7.7 W
--------------------------	-------

