

Product information 74Q WD3 LED3300-830 ETDD
TOC: 6863351



Luminaire type

Square wall and ceiling luminaire with rounded corners.

Applications

For entrance areas, corridors, stairways, lounges, hotels, restaurants and residential zones.

Mounting methods

For wall or ceiling mounting.

Optical system

Matt diffuser with finely structured surface, uniformly illuminated.

LED system

Luminaire luminous flux 3200 lm, connected load 31 W, luminous efficiency of luminaire 103 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index Ra > 80. Service life L₈₀ (t_q 25 °C) = 50,000 h.

Luminaire body


Luminaire body of sheet steel, white, powder-coated. Diffuser of PMMA. Large construction, 520mm x 520mm. Permissible ambient temperature (ta): -20 °C - +25 °C.

Electrical version

With electronic transformer, digitally dimmable (DALI).

Specification text

Square wall and ceiling luminaire with rounded corners. For wall or ceiling mounting. Matt diffuser with finely structured surface, uniformly illuminated. Luminaire luminous flux 3200 lm, connected load 31 W, luminous efficiency of luminaire 103 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index Ra > 80. Service life L₈₀ (t_q 25 °C) = 50,000 h. Luminaire body of sheet steel, white, powder-coated. Diffuser of PMMA. Large construction, 520mm x 520mm. Permissible ambient temperature (ta): -20 °C - +25 °C. Safety class I, protection rating IP40, impact resistance IK02/0,2 J, glow wire resistance 650 °C. With electronic transformer, digitally dimmable (DALI).



Colour	white (...01)
Weight	3.05 kg
Safety class	I
Hot wire test	650 °C
Impact resistance	0,2 J
Degree of protection	IP40
LFEC	F0
Cibse	BZ 4/75/BZ 5
LOR	1,00

