

**Product information 74Q WD1 LED1000-830 ET**  
**TOC: 6861140**



**Luminaire type**

Square wall and ceiling luminaire with rounded corners.

**Applications**

For entrance areas, corridors, stairways, lounges, hotels, restaurants and residential zones.

**Mounting methods**

For wall or ceiling mounting.

**Optical system**

Matt diffuser with finely structured surface, uniformly illuminated.

**LED system**

Luminaire luminous flux 1400 lm, connected load 16 W, luminous efficiency of luminaire 88 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index  $R_a > 80$ . Service life  $L_{80}(t_q 25^\circ\text{C}) = 50,000$  h.

**Luminaire body**


Luminaire body of sheet steel, white, powder-coated. Diffuser of PMMA. Small construction, 320mm x 320mm. Permissible ambient temperature ( $t_a$ ):  $-20^\circ\text{C} - +25^\circ\text{C}$ .

**Electrical version**

With electronic transformer, switchable.

**Specification text**

Square wall and ceiling luminaire with rounded corners. For wall or ceiling mounting. Matt diffuser with finely structured surface, uniformly illuminated. Luminaire luminous flux 1400 lm, connected load 16 W, luminous efficiency of luminaire 88 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index  $R_a > 80$ . Service life  $L_{80}(t_q 25^\circ\text{C}) = 50,000$  h. Luminaire body of sheet steel, white, powder-coated. Diffuser of PMMA. Small construction, 320mm x 320mm. Permissible ambient temperature ( $t_a$ ):  $-20^\circ\text{C} - +25^\circ\text{C}$ . Safety class I, protection rating IP40, impact resistance IK02/0,2 J, glow wire resistance 650 °C. With electronic transformer, switchable.



Colour	<b>white ( ...01)</b>
Weight	<b>1.05 kg</b>
Safety class	<b>I</b>
Hot wire test	<b>650 °C</b>
Impact resistance	<b>0,2 J</b>
Degree of protection	<b>IP40</b>
LFEC	<b>F0</b>
Cibse	<b>BZ 5</b>
LOR	<b>1,00</b>

