

**Product information 74Q WD2 LED2000-830 ETDD**  
**TOC: 6861551**



**Luminaire type**

Square wall and ceiling luminaire with rounded corners.

**Applications**

For entrance areas, corridors, stairways, lounges, hotels, restaurants and residential zones.

**Mounting methods**

For wall or ceiling mounting.

**Optical system**

Matt diffuser with finely structured surface, uniformly illuminated.

**LED system**

Luminaire luminous flux 2200 lm, connected load 21 W, luminous efficiency of luminaire 105 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index  $R_a > 80$ . Service life  $L_{80}(t_q 25^\circ\text{C}) = 50,000$  h.

**Luminaire body**


Luminaire body of sheet steel, white, powder-coated. Diffuser of PMMA. Mid-sized-construction, 420mm x 420mm. Permissible ambient temperature ( $t_a$ ):  $-20^\circ\text{C} - +25^\circ\text{C}$ .

**Electrical version**

With electronic transformer, digitally dimmable (DALI).

**Specification text**

Square wall and ceiling luminaire with rounded corners. For wall or ceiling mounting. Matt diffuser with finely structured surface, uniformly illuminated. Luminaire luminous flux 2200 lm, connected load 21 W, luminous efficiency of luminaire 105 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index  $R_a > 80$ . Service life  $L_{80}(t_q 25^\circ\text{C}) = 50,000$  h. Luminaire body of sheet steel, white, powder-coated. Diffuser of PMMA. Mid-sized-construction, 420mm x 420mm. Permissible ambient temperature ( $t_a$ ):  $-20^\circ\text{C} - +25^\circ\text{C}$ . Safety class I, protection rating IP40, impact resistance IK02/0,2 J, glow wire resistance 650 °C. With electronic transformer, digitally dimmable (DALI).



file TX054540  
 UGR I = 18.8  
 UGR q = 18.8  
 LFEC = F0

— c0-c180  
 — c90-c270



Colour	white ( ...01)
Weight	1.92 kg
Safety class	I
Hot wire test	650 °C
Impact resistance	0,2 J
Degree of protection	IP40
LFEC	F0
Cibse	BZ 5
LOR	1,00

