

Product information 74R WD3 LED3300-830 ET
TOC: 6859940



Luminaire type

Round surface-mounted LED luminaire with opal PMMA diffuser.

Applications

For entrance areas, corridors, stairways, lounges, hotels, restaurants and residential zones.

Mounting methods

For wall or ceiling mounting.

Optical system

With round, spherically-shaped diffuser, slightly flattened on the luminaire head, opal.

LED system

Luminaire luminous flux 3000 lm, connected load 30 W, luminous efficiency of luminaire 100 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index $R_a > 80$. Service life $L_{80} (t_q 25\text{ }^\circ\text{C}) = 50,000\text{ h}$.

Luminaire body


Luminaire body of sheet steel, white, powder-coated. Diameter of diffuser $\varnothing 520\text{ mm}$.

Electrical version

With electronic transformer, switchable.

Specification text

Round surface-mounted LED luminaire with opal PMMA diffuser. For wall or ceiling mounting. With round, spherically-shaped diffuser, slightly flattened on the luminaire head, opal. Luminaire luminous flux 3000 lm, connected load 30 W, luminous efficiency of luminaire 100 lm/W. Light colour warm white, colour temperature 3000 K, colour rendering index $R_a > 80$. Service life $L_{80} (t_q 25\text{ }^\circ\text{C}) = 50,000\text{ h}$. Luminaire body of sheet steel, white, powder-coated. Diameter of diffuser $\varnothing 520\text{ mm}$. Safety class I, protection rating IP40, impact resistance IK02/0,2 J, heat resistance $650\text{ }^\circ\text{C}$. With electronic transformer, switchable.



file TX051327
 UGR I = 19.7
 UGR q = 19.7
 LFEC = F0

— c0-c180
 — c90-c270



Colour	white (...01)
Weight	2.5 kg
Safety class	I
Hot wire test	650 °C
Impact resistance	0,2 J
Degree of protection	IP40
LFEC	F0
Cibse	BZ 5
LOR	1,00

